



Ekostik Industries Sdn. Bhd.



uPVC Window



Gap Between Wall & Cabinet



Perimeter Sealing



Wood Skirting



EK-123 Ultra Flex Gap Sealant

EK-123 Ultra Flex Gap Sealant is a premium and highly elastic acrylic sealant, suitable for both external and internal sealing applications. It is formulated with enhanced UV resistance property and can withstand up to ±25% movement. It is paintable and formulated for sealing gaps and joints where high movements or vibrations are expected.

APPLICATION

It is ideal for external & internal sealing applications. It is good for sealing of building joints that are subject to movement (door and window joints, cabinet and wardrobe installation, skirting of wood flooring, etc.). Suitable for various substrates (metal, PVC, wood, concrete, gypsum boards, reinforced cement boards, marble, etc.).

APPLICABLE TEST / STANDARD

- ASTM C920 & ASTM C719, Type S, Grade NS, Class 25, Use NT, M
- Low VOC - USEPA Method 24 and SCAQMD Method 304-91 under SCAQMD Rule 1168

FEATURES

- ±25% Movement capability
- Exterior & Interior sealant applications
- Paintable
- Permanently flexible & easy clean up
- Waterproof upon curing

Product Code	Content	Carton Quantity
EK-123	450 g	24/Carton

Colour: White